

Product datasheet

Specifications



TeSys GV3 - auxiliary contact - 1 NO + 1 NC early-break

Local distributor code:

381797964

GV3A01

⚠ Discontinued on: 27 Oct 2021

EAN Code: 3389110343335

⚠ Discontinued

Main

Range	TeSys
Device short name	GV3A
Product or component type	Auxiliary contact block
Product compatibility	GV3ME
Mounting location	Right side
Pole contact composition	1 NO + 1 NC
Quantity per set	Set of 10

Complementary

[Ui] rated insulation voltage	600 V conforming to UL 508 690 V conforming to IEC 60947-1 600 V conforming to CSA C22.2 No 14
[Ue] rated operational voltage	48...690 V AC 24...220 V DC
[Ith] conventional free air thermal current	6 A
Mechanical durability	100000 cycles
Protection type	GB2CB... circuit breaker GG fuse 6 A
Rated operational power in VA	350 VA at 48 V AC-11 - electrical durability: 100000 cycles 700 VA at 440 V AC-11 - electrical durability: 100000 cycles 700 VA at 500 V AC-11 - electrical durability: 100000 cycles 400 VA at 690 V AC-11 - electrical durability: 100000 cycles 500 VA at 110...127 V AC-11 - electrical durability: 100000 cycles 800 VA at 220...240 V AC-11 - electrical durability: 100000 cycles 850 VA at 380...415 V AC-11 - electrical durability: 100000 cycles
Rated operational power in W	180 W at 24 V DC-11 - electrical durability: 100000 cycles 240 W at 48 V DC-11 - electrical durability: 100000 cycles 180 W at 60 V DC-11 - electrical durability: 100000 cycles 140 W at 110 V DC-11 - electrical durability: 100000 cycles 120 W at 220 V DC-11 - electrical durability: 100000 cycles

Environment

Environmental characteristic	Normal environment
------------------------------	--------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Logistical informations

Country of origin	FR
-------------------	----

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
EU RoHS Directive	Compliant By Exemption

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins